

LED PROGRAM - LUX



GUIDE DE SELECTION / GUÍA DE SELECCIÓN

 Lighting Technology for Industry LUX SERIES 	STRIP / REGLETAS / APPLIQUE			
	 P. 4-5	 P. 6-7	 P. 8-9	 P. 6-7
	R32 - MDS	R56	R70	R91
DIMENSIONS DIMENSIONES DIMENSIONS mm length x width x height largo x ancho x altura large x ample x hauteur	230x32x23 320x32x23	350x 56 x43 640x 56 x43 930x56 x43 1220x56 x43	342x 70 x58 604x 70 x58 877x 70 x58 340x 70 x58 522x 70 x58 877x 70 x58	350x 91 x46 640x 91 x46 930x 91 x46 1220x 91 x46
IP PROTECTION	IP673	IP67	IP69K	IP69K
POWER SUPPLY ALIMENTACIÓN TENSION ALIMENTATION	24V AC/DC 100 - 220V AC	24VDC	24VDC	24VAC 24VDC
 Lighting Technology for Industry LUX SERIES 	FLEX / FLEXOS / FLEXIBLE			
	 P. 10-11	 P. 12	 P. 13	 P. 14-15
	36	74	75	
DIMENSIONS DIMENSIONES DIMENSIONS mm length largo large	500	spot 465 520 620 820	500 700	500 spot 215+215 400+400
IP PROTECTION	IP65	IP20	IP20	IP65
POWER SUPPLY ALIMENTACIÓN TENSION ALIMENTATION	100 - 240V AC	12/24 VAC/DC 220V - 240V AC	100 - 240V AC	100 - 240V AC 24V AC/DC

LED PROGRAM LUX

GUIDE DE SELECTION / GUÍA DE SELECCIÓN

TUBES / TUBOS / TUBES

	
P. 49-53	P. 20-21
1230 TUBE	TL7
Ø70	380xØ70 658xØ70 958xØ70
IP67	IP67
24VAC	100V ~260V
220-240V AC	24V AC/DC

PROLUX SERIES LED SOLUTIONS



BLF
P. 33



P. 34

FLL

ARMS / BRAZOS / BRAS

		
P. 14-15	P. 16-17	P. 18-19
80	114	125
spot 280+280 380+380	spot 280 220+220 280+280 380+380 220+220+220 280+280+280	spot 280 220+220 280+280 380+380 -
IP65	IP65	IP65
220V -240V AC	24V AC/DC	220V -240V AC
		24V AC/DC
		100 -240V AC

UNI SECTION



DQ
P. 30